

## TECHNICAL INFORMATION

### OSIXO® Anti-Squeak Aerosol

**OSIXO® Anti-Squeak Aerosol** is a Perfluoropolyether (PFPE) in a special solvent.

By bringing the active substances into a solvent, a multiplicity of application possibilities is offered. The spraying ability for example enables a minimum dosage with optimal achievement. The combination of the efficient active substances and the easy handling as well as the safe and clean application makes **OSIXO® Anti-Squeak Aerosol** an outstanding product.

**OSIXO® Anti-Squeak Aerosol** has very good non-adhesive characteristics as well as an outstanding stability. Extremely inert, non-flammable, environmental safe, resistant against nearly all chemical substances, non-migrating, FCKW- and Silicon free. Compatible with all elastomers and polymers.

The product can be applied on a multiplicity of surfaces and is characterized by two special properties:

1. low coefficient of friction,
2. excellent separation and non-adhesive characteristic.

#### Application:

**OSIXO® Anti-Squeak Aerosol** should be applied on clean, dry and grease-free surfaces. Once applied, the coating is resistant to most solvents.

**OSIXO® Anti-Squeak Aerosol** can only be removed with special solvents.

#### Typical properties:

PFPE:	100%
Density @ 0°C:	1,94 g/cm <sup>3</sup>
Density @ 20°C:	1,91 g/cm <sup>3</sup>
Viscosity @ 20°C:	550 cSt
Estimatet useful temperatur range in °C:	-36 bis 204
Appearance:	clear liquid
Odor:	odorless